

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
2 October 2003 (02.10.2003)

PCT

(10) International Publication Number
WO 03/079851 A1

(51) International Patent Classification⁷: **A47B 53/02**,
96/00

(21) International Application Number: PCT/AU03/00360

(22) International Filing Date: 26 March 2003 (26.03.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PS 1361 26 March 2002 (26.03.2002) AU

(71) Applicant (for all designated States except US):
GLIDESTORE FREETRACK PTY LTD [AU/AU]; 48
Fullarton Road, Norwood, S.A. 5067 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **PARKER, Brian**,

Maurice [AU/AU]; Dexion Adelaide, Building 7, 938
South Road, Edwardstown, S.A. 5039 (AU). **CAMP-**
BELL, George, Giles [AU/AU]; Proen Design Australia
Pty Ltd, 157 Burbridge Road, Hilton, S.A. 5033 (AU).


(74) Agent: **MADDERNS**; Level 1, 64 Hindmarch Square,
Adelaide, S.A. 5000 (AU).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD,
SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US,
UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: DRIVE MECHANISM FOR A TRACK MOUNTED BODY



(57) Abstract: A drive mechanism for a body (11, 12) where the body (11, 12) has a plurality of load bearing and track engaging wheels (15) that allow the body (11, 12) to move back and forth along a track (15) that comprises an actuator (18) attached to the body (11, 12) that is manually or mechanically driven, a non-load bearing drive wheel (24) that is attached with respect to the body (11, 12) so that it engages a stationary surface adjacent the body (11, 12) and a drive coupling means, (20, 22) between the actuator (18) and the drive wheel (24) wherein actuation of the actuator (18) causes rotation of the drive wheel (24) which moves the body (11, 12) along the tracks (14). The invention provides a convenient means of attaching a drive mechanism to a body (11) and (12) to enable easier movement of track mounted bodies.

WO 03/079851 A1



ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

— with amended claims and statement

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

DRIVE MECHANISM FOR A TRACK MOUNTED BODY

This invention relates to a drive mechanism for a track mounted body and in particular to a mechanism that enables movement of the body along the tracks without the use of a load bearing drive wheel.

BACKGROUND OF THE INVENTION

An example of where the invention will find application are track mounted shelving or cabinet units. Such shelving units are designed to provide compact storage by having the shelving units abut against one another with only one access opening being provided within which the shelves can be accessed. The shelves can be separated by moving them along the track to open up access at different points along the assembled shelves.

In many instances, shelves are moved manually although it is common to provide a manual crank mechanism or electric drive means to move the shelves. This is particularly necessary when each shelving unit carries a heavy load.

The conventional means of providing a drive to each of the shelves is to connect the track mounted wheels to some form of drive means. This means that an axle extends across the base of each shelf to which the wheels are mounted. The shaft is then connected to some form of independent drive means which may be a manually rotated handle or an electric motor driven through a reduction gear box.

The need to mount a shaft within the base of the shelf unit results in added cost and complexity to the shelving unit. It would be desirable to have a drive mechanism that could be easily fitted to shelving units that were designed to be manually moved. Accordingly, it is an object of this invention to provide such an arrangement that meets this objective and overcomes the above mentioned problems.

SUMMARY OF THE INVENTION

In one form, the invention is a drive mechanism for a body, wherein said body has a plurality of load bearing track engaging wheels that allow said body to move back and forth along a track, that comprises,

an actuator attached to said body that is manually or mechanically driven,

a non-load bearing drive wheel that is attached with respect to said body so that it engages a stationary surface adjacent said body, and

a drive coupling means between said actuator and said drive wheel wherein actuation of said actuator means causes rotation of said drive wheel which moves said body along said tracks.

The above invention avoids the need to have a drive axle mounted through the base of each shelf unit. In addition, it enables a simple arrangement to be attached to an existing shelf unit to convert it from a shelf unit that needs to be manually pushed along the tracks to a unit that incorporates a drive mechanism.

The actuator preferably is a manually rotated capstan wheel or a crank but the drive wheel could equally be driven by an electric motor via a reduction gear box.

The drive wheel applies force to move the body by pushing against the surface or ground on which the body is mounted. Preferably, the periphery of the drive wheel comprises a high friction material such as a polyurethane material and surface against which the periphery of the wheel engages may also be roughened or have a high coefficient of friction to avoid slippage of the drive wheel.

Preferably, the drive coupling between the actuator and drive wheel includes reduction gearing. The gearing can include many different types of components such as tooth belts, v-belts, meshing gear wheels and the like. One preferred arrangement is the use of a first belt that extends from the drive shaft towards the base of the body. This belt drives a first pulley wheel that in turn drives a second pulley wheel and there is a belt

that extends from the second pulley to a pulley wheel that is attached to the drive wheel which in turn rotates the drive wheel.

In order to fully understand the invention, a preferred embodiment will be described. However, it should be realised that the invention is not necessarily restricted to the precise details of this embodiment. In particular, the embodiment is described in relation to application of the invention to a shelving system. However, there may be other applications to which the invention could be equally suited.

The invention is illustrated in the accompanying drawings in which

Figure 1 shows three shelf units, two of which are track mounted,

Figure 2 shows an exploded view of a drive mechanism and covers that are attached to the side of a shelf unit,

Figure 3 shows a perspective view of an assembled drive mechanism attached to the side of a shelf unit,

Figure 4 shows an exploded view of a drive mechanism, and

Figure 5 shows a cross-section of a carriage within which gearing and the drive wheel are mounted.

Referring to Figure 1, there are three shelf units 10, 11 and 12 with shelves 13. Shelf units 11 and 12 are mounted to tracks 14 via wheels 15. Tracks 14 provide a longitudinal recess within which the wheels 15 locate. A pair of wheels 15 are used at each side of the shelf units 11 and 12 and are rotatably mounted within a housing which is attached at each side of the unit 11 and 12.

The shelf unit 10 is an end shelf unit and therefore is fixed with respect to the tracks 14. Shelf units 11 and 12 are moved along the tracks 14 to provide access between various pairs of shelves. For example, shelf unit 11 can be moved so as to open up access between shelf unit 11 and 10.

Figure 2, 3 and 4 show more detailed views of the drive mechanism. It has an actuator that comprises a drive shaft 17 to which a hand operated wheel 18 is attached. The drive shaft 17 is rotatably secured to a column 19 with column 19 attached to the side of the shelf unit.

A first drive belt 20 extends from a pulley wheel 18a on the wheel 18 downwardly to a carriage 27 that is located towards the base of the shelf unit 11 and 12. The belt 20 is an internal tooth belt and the pulley wheel 18a on the wheel 18 is toothed to engage with the belt 20. For ease of drafting purposes, the teeth on the belt 20 and pulley wheels are not drawn.

The carriage 27 has mounted to it a first pulley wheel set comprising a first pulley wheel 16 and a second pulley wheel 21. In addition, the drive wheel 24 is also mounted within the carriage 27. The belt 20 locates around the first pulley wheel 16 which is connected to the second pulley wheel 21. A second tooth belt 22 locates around the second pulley wheel 21 and drives a third pulley wheel 23 which is connected to the drive wheel 24. As can be seen from the drawings, the first pulley wheel 16 is a larger diameter than the second pulley wheel 21. The combination of the pulley wheel 18a on the handle 18 and its diameter difference with the first pulley wheel 16 and the diameter difference between the pulley wheel 16 and the second pulley wheel 21 provides the required reduction in gearing.

The carriage 27 is pivotally attached to the side of the shelf unit via a pivot connection 28. In this embodiment the pivot connection 28 is secured to a plate 29 that is attached to the column 19 and the side of the shelving unit 11 and 12.

The carriage 27 is a u-shaped bracket between which the first and second pulley wheels 16 and 21 and the drive wheel 24 and third drive pulley wheel 23 are rotatably mounted. The axle 36 of the drive wheel 24 is rotatably mounted to an inner carriage 37. The inner carriage 37 locates within the carriage 27. Elongate slots 38 are provided in

the carriage 27 through which the ends of the axle 36 locate. Circips 39 located on each end of the axle 36 and retain the axle 36 within the carriage 27. This enables the inner carriage 37 to slide with the carriage 27 and this movement is controlled by threaded bolt 40 which locates within a nut 41 in the end of the inner carriage 37. Rotation of the bolt 40 enables the inner carriage 37 to be moved to enable tightening the belt 22.

A spring 30 applies a downward force to the carriage 27 so that the carriage 27 is rotated in an anti clockwise direction. This acts to force the drive wheel 24 against the linear strip 26 of the drive wheel track and to tighten belt 20. A bracket 31 is part of the plate 29 and the carriage 27 has a flange 32 that locates beneath the bracket 31. The spring 30 is held under compression between the bracket 31 and the flange 32 so that the necessary rotated force is applied to the carriage 27. The bracket 31 and flange 32 are on one side of the carriage 27. However, they may be located centrally over the carriage 27 so that no eccentric force is applied to the carriage. This will prevent side loading being applied to the drive wheel 24.

The drive wheel track 25 is preferably co-extruded with the track 14. The linear strip 26 of the drive wheel track 25 is preferably roughened or has an abrasive strip adhered to it. The drive wheel 24 preferably has a polyurethane tyre which, in combination with the linear strip 26, provides maximum grip. This grip, in combination with the force applied by the spring 30 is sufficient to ensure that the drive wheel 24 does not slip with respect to the linear strip 26.

Although this preferred embodiment uses a track 25, the invention would equally work without such a track where the drive wheel 24 engages a floor such as a linoleum surface.

The advantage of the pivotally mounted carriage 27 is that a perfectly level track is not required. The floor surface or track 25 may have undulations which are accommodated by the spring 30 and movement of the carriage 27.

As seen in Figure 2, a first cover 33 locates over the side of the shelf units 11 and 12 over the column 19 and a second cover 34 locates over the first cover 33 and extends from the handle 18 down to and over the carriage 27.

The gearing ratio gives adequate speed of movement of the shelving unit while at the same time not requiring excessive effort to be applied to the hand operated wheel 18.

It will be clear from the above description that the invention provides a unique means of providing a drive mechanism for track mounted bodies such as shelf units. The drive mechanism does not make use of a load bearing wheel and does not require the installation of an axle through the base of the unit moving along the track.

The design is useful in that it can be manufactured so as to fit to units that are designed to be manually moved. However, the design could equally be incorporated into the shelving unit rather than being a bolt on assembly.

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A drive mechanism for a body, wherein said body has a plurality of load bearing track engaging wheels that allow said body to move back and forth along a track, that comprises,
an actuator attached to said body that is manually or mechanically driven,
a non-load bearing drive wheel that is attached with respect to said body so that it engages a stationary surface adjacent said body, and
a drive coupling means between said actuator and said drive wheel wherein actuation of said actuator causes rotation of said drive wheel which moves said body along said tracks.
2. A drive mechanism according to claim 1 wherein said drive wheel frictionally engages said surface.
3. A drive mechanism according to claim 2 wherein the periphery of said drive wheel comprises a material having a high friction co-efficient.
4. A drive mechanism according to claim 3 wherein said material comprises polyurethane.
5. A drive mechanism according to any one of the claims 1 to 4 further comprising a means of biasing said drive wheel towards said surface.
6. A drive mechanism according to claim 5 wherein said means comprises a carriage to which said drive wheel is mounted that is pivotally mounted with respect to said body and a spring mounted between said carriage and said body that urges said carriage towards said surface.
7. A drive mechanism according to any one of the preceeding claims further

comprising reduction gearing between said actuator and said drive wheel.

8. A drive mechanism according to any one of the preceeding claims wherein said drive coupling comprises a belt extending between said actuator and said drive wheel.

9. A drive mechanism according to claim 8 further comprising an intermediate pair of pulleys with said belt extending to a first of said pulleys with a second belt extending from a second of said pulleys to said drive wheel.

10. A drive mechanism according to anyone of the preceeding claims wherein said actuator comprises a manually operated crank.

11. A drive mechanism according to claim 10 wherein said crank comprises a wheel.

12. A drive mechanism for a body, wherein said body has a plurality of load bearing track engaging wheels that allow said body to move back and forth along a track that comprises;

a non-load bearing drive wheel that is attached with respect to said body so that it frictionally engages a stationary surface adjacent said body, and drive means for rotating said drive wheel to move said body along said tracks.

13. A plurality of track mounted cabinets using a drive mechanism according to any one of the preceeding claims wherein each said cabinet comprises a body with a said drive mechanism attached to each said cabinet.

14. A track mounted cabinet according to claim 13 wherein said surface is an elongate track extending along the length of said cabinets that is engaged by said drive wheel.

15. Track mounted cabinets according to claim 14 wherein said elongate track is attached to any one of said tracks supporting said cabinets.
16. A drive mechanism substantially as herein described with reference to the accompanying drawings.
17. A plurality of track mounted cabinets substantially as herein described with reference to the accompanying drawings.

AMENDED CLAIMS

[received by the International Bureau on 9 July 2003 (09.07.03);
original claims 1 to 13 amended (3 pages)]

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A drive mechanism for a body, wherein said body has a plurality of load bearing track engaging wheels that allow said body to move back and forth along a track, that comprises,
an actuator attached to said body that is manually or mechanically driven,
a non-load bearing drive wheel that is attached with respect to said body so that it engages a stationary surface adjacent said body, said drive wheel and said actuator located on the same side of said track, and
a drive coupling means between said actuator and said drive wheel wherein actuation of said actuator causes rotation of said drive wheel which moves said body along said tracks.
2. A drive mechanism according to claim 1 wherein said drive wheel frictionally engages said surface.
3. A drive mechanism according to claim 2 wherein the periphery of said drive wheel comprises a material having a high friction co-efficient.
4. A drive mechanism according to claim 3 wherein said material comprises polyurethane.
5. A drive mechanism according to any one of the claims 1 to 4 further comprising a means of biasing said drive wheel towards said surface.
6. A drive mechanism according to claim 5 wherein said means comprises a carriage to which said drive wheel is mounted that is pivotally mounted with respect to said body and a spring mounted between said carriage and said body that urges said carriage towards said surface.

7. A drive mechanism according to any one of the preceding claims further comprising reduction gearing between said actuator and said drive wheel.
8. A drive mechanism according to any one of the preceding claims wherein said drive coupling comprises a belt extending between said actuator and said drive wheel.
9. A drive mechanism according to claim 8 further comprising an intermediate pair of pulleys with said belt extending to a first of said pulleys with a second belt extending from a second of said pulleys to said drive wheel.
10. A drive mechanism according to anyone of the preceding claims wherein said actuator comprises a manually operated crank.
11. A drive mechanism according to claim 10 wherein said crank comprises a wheel.
12. A drive mechanism for a body, wherein said body has a plurality of load bearing track engaging wheels that allow said body to move back and forth along a track that comprises;
a non-load bearing drive wheel that is attached with respect to said body so that it frictionally engages a stationary surface adjacent said body, and
drive means for rotating said drive wheel to move said body along said tracks, wherein said drive means and said drive wheel are located on the same side of said track.
13. A plurality of track mounted cabinets using a drive mechanism according to any one of the preceding claims wherein each said cabinet comprises a body with a said drive mechanism attached to each said cabinet.

14. A track mounted cabinet according to claim 13 wherein said surface is an elongate track extending along the length of said cabinets that is engaged by said drive wheel.
15. Track mounted cabinets according to claim 14 wherein said elongate track is attached to any one of said tracks supporting said cabinets.
16. A drive mechanism substantially as herein described with reference to the accompanying drawings.
17. A plurality of track mounted cabinets substantially as herein described with reference to the accompanying drawings.

STATEMENT UNDER ARTICLE 19(1)

The applicant forwards herewith replacement pages 2, 7, 8 and 9 for originally filed pages 2, 7, 8 and 9.

These claims have been amended to further distinguish the claimed invention from the prior art listed in the International Search Report.




Fig 1

2/5




Fig 2

3/5




Fig 3

4/5




Fig 4

5/5




Fig 5

INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU03/00360

A. CLASSIFICATION OF SUBJECT MATTERInt. Cl. ⁷: A47B 53/02, A47B 96/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
AU: IPC7 - B61B 13/02; B61C 11/00, 11/04, 15/02; B66C 9/00, 9/14Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
WPAT: IPC7 -A47B 53/02, A47B 96/00 and Keywords: Drive, Wheel, Roller, Move, Rail, Track**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 934891 A (KULTNER) 21 August 1963 Page 3, Line 3-45, Figure 6	1-17
X Y	WO 9802063 A (CONSTRUCTOR BRUYNZEEL B.V.) 22 January 1998 Figure 2; Page 6, line 17-31.	1-4, 5-17 5-6
X Y	US 6112917 A (BAKER et al.) 5 September 2000 Figure 2, Column 6, line 51 to Column 7, line 26.	1-4, 5-17 5-6
X Y	EP 0779047 A (VAN GEEL GROUP B.V.) 18 June 1997 Whole Document.	1-4, 5-17 5-6

☒ Further documents are listed in the continuation of Box C☒ See patent family annex

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier application or patent but published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search 2 May 2003	Date of mailing of the international search report 15 MAY 2003
Name and mailing address of the ISA/AU AUSTRALIAN PATENT OFFICE PO BOX 200, WODEN ACT 2606, AUSTRALIA E-mail address: pct@ipaustalia.gov.au Facsimile No. (02) 6285 3929	Authorized officer VENKAT IYER Telephone No : (02) 6283 2144

INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU03/00360

C (Continuation).

DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	AU 76190/98 A (BOMAC ENGINEERING PTY LTD) 11 February 1999 Figure 1; Page 4, line 9 to Page 5, line 24.	1-9, 12-17
Y,P	JP 2002265017 (NIPPON YUSOKI CO LTD) 18 September 2002 Figures 1-7	5-6

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/AU03/00360

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report		Patent Family Member	
GB	934891	NONE	
WO	9802063	EP	914050
US	6112917	NONE	
EP	779047	NONE	
AU	76190/98	NONE	
JP	2002265017	NONE	
END OF ANNEX			